

MONOBLOC LEVER MIXING TAP

PRODUCT CODE

6742 SLMMT

SEPTEMBER 2016



- SIMPLE EASY TO GRIP LEVER OPERATION
- SEQUENTIAL FLOW
- CERAMIC DISC CARTRIDGE
- ▲ CONTEMPORARY DESIGN
- ▲ HIGH POLISH CHROME FINISH




The monobloc mixing tap features a single lever sequential spray mixer providing cold to hot through 180 degree operation of the lever. The tap incorporates a ceramic disc cartridge. The lever handle is easy to grip and can be operated by either hand or wrist making the tap ideal for those with limited dexterity. The mixer tap is not thermostatic and a proprietary temperature control device such as a thermostatic mixing valve (TMV) should always be used.

Construction

The monobloc mixing tap is manufactured from brass and has a high polish chrome finish. The 180 degree lever operates a ceramic disc cartridge. Supplied with flexible water inlet hoses.

Dimensions



Pressures

Minimum Working Pressure: 0.2 bar Maximum Working Pressure: 6.0 bar Recommended Operating Range: 2.0 to 5.0 bar Flow Rate at 1.0 bar: 7.0l/minute

Order Code 6742 SLMMT



5 Brearley Court, Baird Road, Waterwells Business Park, Quedgeley, Gloucester, GL2 2AF

Tel: 01452 721211 Fax: 01452 721231 web: www.acornthorn.co.uk