



### **Description**

- Model SH641 is our beach shower
- Manufactured from grade 316 stainless steel, 1.6mm thick
- Factory assembled and pre-plumbed
- Choice of 1, 2, 3 or 4 shower heads
- Each shower head is complete with individual timed flow push button valve
- Adjustable run time from 5 to 60 seconds
- Single supply inlet of 19mm diameter copper pipe
- Optional foot sprays also available

### **Includes**

- Heavy duty base steel anchor plate coated with rust preventative
- Removable side access panel held by security type screws
- Heavy duty base mounting flange

### **Delivery**

- Manufactured to order, 14 to 16 working weeks

### **Dimensions**

- **Height (including spray heads):** 1930mm
- **Height:** 1830mm
- **Height (button to floor):** 820mm

### **Delivery**

- Manufactured to order 14 to 16 working weeks

### **Optional Extras**

**SH641-FS** - Foot spray with individual valve timed flow push button valve

### **Where can this be installed?**

- This beach shower is ideal for marine locations, beaches, swimming pools, leisure centres, sports clubs and campsites
- The higher chromium content of this stainless steel helps prevent against any potential corrosion or rusting that can occur

### **Installation Advice**

- Single supply pipe should finish 12.7mm above the anchor plate in a 3/4" NPT male thread
- This will allow fitting of the "O" ring adaptor (provided) to the anchor plate
- Minimum water pressure of 1.2 bar required at the point where the supply enters the column
- Water pressures in excess of 8.0 bar a pressure reducing valve must be fitted
- During freezing temperatures the unit should be drained down to avoid damage to the valves